

PROLINE  
**Stone & Veneer**  
 By NORSE



## 1. Product Name

- Pro-Line Stone Veneer

## 2. Manufacturer

Norse Building Products, Inc.  
 536 Main Street  
 Allenton, WI 53002  
 Phone: 262-629-9330  
 Fax: 262-629-9982  
 E-mail: [josh@norsebuildingproducts.com](mailto:josh@norsebuildingproducts.com)  
 Web: [www.prolinestone.com](http://www.prolinestone.com)

## 3. Product Description

### Basic Use

Pro-Line Stone Veneer is a high-quality manufactured stone veneer used by building professionals and architects. Pro-Line Stone Veneer is used as an adhered, non-load bearing siding or façade in commercial or residential projects, both exterior and interior applications. Common uses include walls (exterior or interior) fireplaces and column wraps. Installation over masonry, wood or metal framed construction. Pro-Line Stone is tested under the most intensive standards in the industry as guided by ICC-ES.

### Composition and Materials

Pro-Line Stone Veneer is created with Portland cement and lightweight aggregates, with admixtures for strength and workability. UV-stable pigments are used for coloring.

### Features and Benefits

- Made for exterior and interior use
- Saturated weight less than 15 pounds per square foot
- ColorArmor Color: 100 percent UV stable colors used in manufacturing
- GripperBack backing of stone for 50 percent more bonding surface area than competitor stone veneer
- Meets and exceeds AC51 testing for strength and durability, including 50 year freeze-thaw testing
- Meets and exceeds industry standards for manufacturing Quality Control processes as evaluated by ICC-ES

### Product Limitations

Pro-Line Stone Veneer is intended to be a wall or façade product. Do not use as pavers or other areas subject to foot or vehicle

traffic. Install above grade and according to *MVMA Adhered Manufactured Stone Veneer Installation Guide*. Salts and other de-icers can damage stone veneer and should not be used on product. Sealers are not recommended. Non-breathable sealers void warranty

### Safety Data Sheets (SDS)

The SDS is available [here](#).

### Types and Dimensions

Pro-Line Stone Veneer is available in 36 styles and patterns. The full Pro-Line Stone Veneer catalog is [here](#).

### Special Features

Color Armor coloring: only 100 percent UV stable pigments used in manufacturing

GripperBack backing: 50 percent more bonding surface area than competitor's stone veneer.

### Accessories/Options:

Matching accessories for all major color patterns: Address stones; hearthstones, keystone, light and utility boxes; quoins; sills; lintels and trimstone: [here](#).

## 4. Technical Data

### Applicable Standards

#### International Building Code (IBC)

- **AC51** Acceptance Criteria for Precast Stone Veneer

### Approvals

- Compliance with 2015, 2012 and 2009 International Building Code (IBC)
- Compliance with 2015, 2012 and 2009 International Residential Code (IRC)
- ICC-ES Evaluation Report (ESR-3565)



## 5. Installation

### Preparatory Work

Pro-Line Stone Veneer must be installed over a lath and mortar scratch coat or applied directly to concrete and masonry. Underlying sheathing must be structurally sound and capable of supporting stone veneer

### Installation Instructions

Use manufacturer's provided and [these instructions](#).

### Weather/Ambient Considerations

Stone must be installed in temperatures above 45 degrees F for proper mortar adhesion. Tented or heated areas in cooler temps are required.

## 6. Availability and Cost

Contact manufacturer for pricing and availability,



## 7. Warranty

A 50-year limited warranty is offered. Additional information is [here](#).

## 8. Maintenance

No maintenance is required.

## 9. Technical Services

Norse Building Products provides technical services, please contact the manufacturer for technical support.

## 10. Filing Systems

- ConstructConnect
- Additional product information is available from the manufacturer upon request ↪

